

GrowControl™ Model Comparison Chart



GC-Pro



GC-ProXL/M



Max # of Outputs (included)	20 (12) <i>24Vdc terminals</i>	40 (16) <i>24Vdc terminals</i>
Max. # of Sensor Ports (included)	4 (2)	6 (4)
Expansion Ports	1 Slot	3 Slots
Sensors Accepted	Standard: 2 Climate + 2 Hydro "C" Model: 3 Climate + Weather "Q" Model: 4 Climate or 3 + Weather	Standard: 3 Climate + 2 Hydro + Weather "C" Model: 3 Climate + Weather "Q" Model: 4 Climate + Weather
Sensors Included	1x Aspirated Indoor Climate Temp/RH/Light (CO ₂ optional)	
Output Options	RX / CX / RD Relays MX Motor Relays AD1 / AD2 / AD4 Dosing Pumps	
Zones	1 to 4 (recommended 1 – 2)	1 to 4
Free PC Software	●	
Serial Port (RS-232)	●	
Ethernet Port	○	
AgrowTouch 4" Screen	○	
Basic Climate Control	●	
CO₂ ppm Control	●	
Nutrient/pH Control	● (Standard Model only)	
Weather Station	○	
Vent/Shade/Curtain Control	● ("C" Model only)	
Multi-Stage Climate Control	● ("C" Model only)	



Standard



Optional



Not Available